SATEL J J TE COMMUNICA'] '] ON ANTENNAS

J ohn Huang

Jet Propulsion I abor atory California 1 nstitute of Technology Pasadena, California 91109

Satel 1 ite communication antenna systems can be separated into the space segment and the ground segment.. 1 n the space segment, the antennas are used for either deep space exploration or Earth orbiting application. In the ground segment, the antenna systems can be categorized into mobile and fixed-st ation applications. The spacecraft general 1 y requires its antennas to be 1 ow in mass and smallin volume so that they can f it. appropriately into the 1 aunch vehicle. The ground mobile units also require the antennas] n addition, these antennas must be I ow in to be small in size. cost so that they can be affordable to users. The ground fixed stations) on the other hand, generally prefer their antennas to be large in size and able to handle very high RF power. In all these applications, the most frequently used antenna type is the para bolic dish which involves the technologies of Cassegrain, shaped Cassegrain, multibeam, contourbeam, multi-frequency, frequency selective surface (FSS), beam waveguide, deployable surface, meshed surface, etc. Other than the dish type, the antennas that are sometimes used for satellite communications are the phased array, t he active phased array, the low-prof i 1 e printed microst rip array, the waveguide array, the helix, the horn, the lens array, etc.

^{*} The re.search described in this paper was carried out. by the Jet Propulsion 1 aboratory, California 1 nstitute of Technology, under contract with the National Aeronautics and Space Admintration.